

AD-A054 949

SCHOOL OF AEROSPACE MEDICINE BROOKS AFB TEX
A FORTRAN PROGRAM TO FIT A COMPLEX-VALUED TRANSFER FUNCTION.(U)
MAR 78 R C MCNEE, W G JACKSON

F/G 9/2

UNCLASSIFIED

SAM-TR-78-7

NL

| OF |
AD
A054949



END
DATE
FILMED
7-78
DDC

AD A 054949

Report SAM-TR-78-7


FOR FURTHER TRAN



B.S.

A FORTRAN PROGRAM TO FIT A COMPLEX-VALUED TRANSFER FUNCTION

Richard C. McNee, M.S.
William G. Jackson, Jr., M. Stat.



March 1978

Final Report for Period March 1976-May 1976

Approved for public release; distribution unlimited.

DDC FILE COPY

USAF SCHOOL OF AEROSPACE MEDICINE
Aerospace Medical Division (AFSC)
Brooks Air Force Base, Texas 78235



78 06 12 1


NOTICES


This final report was submitted by personnel of the Design and Analysis Branch, Biometrics Division, USAF School of Aerospace Medicine, Aerospace Medical Division, AFSC, Brooks Air Force Base, Texas, under job order 6319-03-24.


When U.S. Government drawings, specifications, or other data are used for any purpose other than a definitely related Government procurement operation, the Government thereby incurs no responsibility nor any obligation whatsoever; and the fact that the Government may have formulated, furnished, or in any way supplied the said drawings, specifications, or other data is not to be regarded by implication or otherwise, as in any manner licensing the holder or any other person or corporation, or conveying any rights or permission to manufacture, use, or sell any patented invention that may in any way be related thereto.

This report has been reviewed by the Information Office (OI) and is releasable to the National Technical Information Service (NTIS). At NTIS, it will be available to the general public, including foreign nations.

This technical report has been reviewed and is approved for publication.


RICHARD C. McNEE, M.S.
Project Scientist


PHELPS P. CRUMP, Ph.D.
Supervisor


ROBERT G. MCIVER
Brigadier General, USAF, MC
Commander

Editor: MARION E. GREEN

UNCLASSIFIED

SECURITY CLASSIFICATION OF THIS PAGE (When Data Entered)

REPORT DOCUMENTATION PAGE		READ INSTRUCTIONS BEFORE COMPLETING FORM
1. REPORT NUMBER SAM-TR-78-7 ✓	2. GOVT ACCESSION NO.	3. RECIPIENT'S CATALOG NUMBER
4. TITLE (and Subtitle) A FORTRAN PROGRAM TO FIT A COMPLEX-VALUED TRANSFER FUNCTION.	5. TYPE OF REPORT PERIOD COVERED Final rept. March 1978 - May 1976	6. PERFORMING ORG. REPORT NUMBER
7. AUTHOR(s) Richard C./McNee, [redacted] William G./Jackson, Jr M.Stat.	8. CONTRACT OR GRANT NUMBER(s)	
9. PERFORMING ORGANIZATION NAME AND ADDRESS USAF School of Aerospace Medicine (BRD) Aerospace Medical Division (AFSC) Brooks Air Force Base, Texas 78235	10. PROGRAM ELEMENT, PROJECT, TASK AREA & WORK UNIT NUMBERS 62202F 6319-03-24	11. REPORT DATE March 1978
11. CONTROLLING OFFICE NAME AND ADDRESS USAF School of Aerospace Medicine (BRD) Aerospace Medical Division (AFSC) Brooks Air Force Base, Texas 78235	12. NUMBER OF PAGES 9	13. SECURITY CLASS. (of this report) UNCLASSIFIED
14. MONITORING AGENCY NAME & ADDRESS (if different from Controlling Office)	15. SECURITY CLASS. (of this report) UNCLASSIFIED	15a. DECLASSIFICATION/DOWNGRADING SCHEDULE
16. DISTRIBUTION STATEMENT (of this Report) Approved for public release; distribution unlimited.		
17. DISTRIBUTION STATEMENT (of the abstract entered in Block 20, if different from Report)		
18. SUPPLEMENTARY NOTES		
19. KEY WORDS (Continue on reverse side if necessary and identify by block number) Transfer Function Nonlinear Estimation		
20. ABSTRACT (Continue on reverse side if necessary and identify by block number) A procedure is given to obtain the estimate of a transfer function with up to eight parameters (gain, delay, 3 zeros, and 3 poles). An example of a subroutine used in conjunction with a program for least-squares estimation of nonlinear parameters is included.		

DD FORM 1 JAN 73 1473 EDITION OF 1 NOV 65 IS OBSOLETE

UNCLASSIFIED

SECURITY CLASSIFICATION OF THIS PAGE (When Data Entered)

317 000

JUN 14 1978

REPORT DOCUMENTATION PAGE	
1. REPORT NUMBER	
2. AUTHOR	
3. TITLE	
4. REPORT NUMBER	
5. AUTHOR	
6. TITLE	
7. REPORT NUMBER	
8. AUTHOR	
9. TITLE	
10. REPORT NUMBER	
11. AUTHOR	
12. TITLE	
13. REPORT NUMBER	
14. AUTHOR	
15. TITLE	
16. REPORT NUMBER	
17. AUTHOR	
18. TITLE	
19. REPORT NUMBER	
20. AUTHOR	
21. TITLE	
22. REPORT NUMBER	
23. AUTHOR	
24. TITLE	
25. REPORT NUMBER	
26. AUTHOR	
27. TITLE	
28. REPORT NUMBER	
29. AUTHOR	
30. TITLE	
31. REPORT NUMBER	
32. AUTHOR	
33. TITLE	
34. REPORT NUMBER	
35. AUTHOR	
36. TITLE	
37. REPORT NUMBER	
38. AUTHOR	
39. TITLE	
40. REPORT NUMBER	
41. AUTHOR	
42. TITLE	
43. REPORT NUMBER	
44. AUTHOR	
45. TITLE	
46. REPORT NUMBER	
47. AUTHOR	
48. TITLE	
49. REPORT NUMBER	
50. AUTHOR	
51. TITLE	
52. REPORT NUMBER	
53. AUTHOR	
54. TITLE	
55. REPORT NUMBER	
56. AUTHOR	
57. TITLE	
58. REPORT NUMBER	
59. AUTHOR	
60. TITLE	
61. REPORT NUMBER	
62. AUTHOR	
63. TITLE	
64. REPORT NUMBER	
65. AUTHOR	
66. TITLE	
67. REPORT NUMBER	
68. AUTHOR	
69. TITLE	
70. REPORT NUMBER	
71. AUTHOR	
72. TITLE	
73. REPORT NUMBER	
74. AUTHOR	
75. TITLE	
76. REPORT NUMBER	
77. AUTHOR	
78. TITLE	
79. REPORT NUMBER	
80. AUTHOR	
81. TITLE	
82. REPORT NUMBER	
83. AUTHOR	
84. TITLE	
85. REPORT NUMBER	
86. AUTHOR	
87. TITLE	
88. REPORT NUMBER	
89. AUTHOR	
90. TITLE	
91. REPORT NUMBER	
92. AUTHOR	
93. TITLE	
94. REPORT NUMBER	
95. AUTHOR	
96. TITLE	
97. REPORT NUMBER	
98. AUTHOR	
99. TITLE	
100. REPORT NUMBER	

A FORTRAN PROGRAM TO FIT A COMPLEX-VALUED TRANSFER FUNCTION

INTRODUCTION

A method is programmed to fit a transfer function with up to eight parameters: gain, delay, 3 leads (or zeros), and 3 lags (or poles). A modified version of a Fortran program by Donald W. Marquardt (1) for least-squares estimation of nonlinear parameters is the basic program used. The program requires a subroutine to define the residual and the partial derivatives of the function to be fitted and to evaluate these real-valued quantities at each of N points. This paper discusses the assumptions used and the structure of the subroutine to fit a complex valued function with a program written to fit real valued functions.

ASSUMPTIONS MADE IN THE METHOD

The norm to be minimized is:

$$\phi = \sum_{i=1}^n |H(j\omega_i) - \hat{H}(j\omega_i)|^2 \quad (1)$$

where ω is the frequency in radians, H is the observed value of the transfer function, and \hat{H} is the predicted value of the transfer function using the estimated values of the parameters.

The observed values can be written as:

$$H(j\omega_i) = U_i + jV_i \quad (2)$$

and the predicted values can be written as:

$$\hat{H}(j\omega_i) = R_i(\theta) + jQ_i(\theta) \quad (3)$$

where θ represents the vector of parameters and the $R_i(\theta)$ and $Q_i(\theta)$ are real functions of these parameters and the frequency. These functions are given in Appendix A for the eight-parameter transfer function considered herein. Using equations 2 and 3, equation 1 can be written as:

$$\phi = \sum_{i=1}^n [U_i - R_i(\theta)]^2 + \sum_{i=1}^n [V_i - Q_i(\theta)]^2 \quad (4)$$

The main program requires that the sum of squares of residuals to be minimized be of the form

1. Marquardt, D. W. An algorithm for least-squares estimation of nonlinear parameters. J Soc Indust Appl Math II (No. 2): 431-441 (1963).

$$\sum \text{Res}^2 = \sum (\text{observed} - \text{function})^2 . \quad (5)$$

In equation 4, the function is $R_i(\theta)$ for the real part and $Q_i(\theta)$ for the imaginary part. These two functions require different computations for the residual and different sets of partial derivatives to be evaluated. These functions and their partial derivatives with respect to the parameters are given in Appendix A for the eight-parameter transfer function.

Under the assumption that the real and imaginary parts of $H(j\omega_i)$ are independent for each ω_i and that the $H(j\omega_i)$ are independent for different ω , the problem of fitting a complex-valued function to n frequencies can be considered as a problem of fitting one of two real-valued functions to $N = 2n$ independent data points. When only ensemble averaging is done to calculate the observed values of the transfer function, the approximate independence of the values at the Fourier frequencies is an immediate extension of the approximate independence for the periodogram. When tapering or smoothing is done, this will no longer be true, except for smoothed estimates at frequencies not using any common unsmoothed value. Therefore, ensemble averaging is the recommended method of obtaining the observed values. When only a single sample is available, the use of the original Bartlett window that involves dividing the sample into several subsamples of equal length and averaging the periodogram estimates from these subsamples is the recommended alternative.

The use of averaging still does not assure any reasonability of the assumption of independence of the real and imaginary parts at the same frequency. This appears to be analytically intractable to show, but preliminary results from some Monte Carlo simulation indicate that the assumption is probably not unreasonable.

Finally, the reasonableness of using equal weights at all frequencies should be considered. Assuming that the variances of the real and imaginary parts of all frequencies are equal, then equal weights should be used. Demonstrating equality of variances appears to be analytically intractable, although preliminary results from the simulation data suggest the assumption may be reasonably sound. Therefore, estimating the parameters of a transfer function by minimizing equation 4 and considering the $2n = N$ data values as independent with equal variances seems to be reasonable.

STRUCTURE OF THE SUBROUTINE

The required standard information available to the subroutine consists of the vector of parameter estimates from the previous iteration, the vector of N values of the dependent variable (Y), the matrix of N values of one or more independent variables (X), and the index of the

point whose residual and partial derivatives are currently being evaluated. The additional information needed for this estimation problem is whether the current value is a real part or imaginary part of an observed value. This is obtained by coding an extra independent variable, 1 if real and 2 if imaginary. Thus each of the N data vectors is made up of three quantities: the real or imaginary part of an observed value, the frequency in radians associated with the observed value, and an indicator of whether the data vector is for a real part or an imaginary part (coded 1 or 2).

Since the real and imaginary parts of the residuals and the partial derivatives are determined separately, the computations in the subroutine are done in two sections, one for the real part and the other for the imaginary part. Therefore, the subroutine is a two-function subroutine with an indicator to specify which function to use. An example of a subroutine which incorporates the ideas described above for the eight-parameter transfer function is shown in Appendix B.

ACCESSION for		
NTTS	Write Section	<input checked="" type="checkbox"/>
DDC	Diff Section	<input type="checkbox"/>
UNANNOUNCED		<input type="checkbox"/>
JUSTIFICATION.....		
BY.....		
DISTRIBUTION/AVAILABILITY CODES		
Dist.	AVAIL. and/or SPECIAL	
A		

APPENDIX A

FUNCTIONS OF THE REAL AND IMAGINARY PARTS OF THE EIGHT-PARAMETER TRANSFER FUNCTION AND THEIR PARTIAL DERIVATIVES WITH RESPECT TO THE PARAMETERS

The transfer function can be written as:

$$\hat{H}(j\omega_1) = \frac{K[1 + \gamma_1(j\omega_1) + \gamma_2(j\omega_1)^2 + \gamma_3(j\omega_1)^3] e^{-j\tau\omega_1}}{[1 + \alpha_1(j\omega_1) + \alpha_2(j\omega_1)^2 + \alpha_3(j\omega_1)^3]}$$

Writing the exponential as:

$$e^{-j\tau\omega_1} = \cos \tau\omega_1 - j \sin \tau\omega_1,$$

multiplying the numerator and denominator by the conjugate of the denominator, and collecting terms gives:

$$\hat{H}(j\omega_1) = R_1 + jQ_1$$

where, dropping the i subscript,

$$R = K[(AB + CD) \cos \tau\omega + (AD - BC) \sin \tau\omega]/Z$$

$$Q = K[(AD - BC) \cos \tau\omega - (AB + CD) \sin \tau\omega]/Z$$

and

$$A = 1 - \alpha_2\omega^2$$

$$B = 1 - \gamma_2\omega^2$$

$$C = \omega(\alpha_1 - \alpha_3\omega^2)$$

$$D = \omega(\gamma_1 - \gamma_3\omega^2)$$

$$Z = A^2 + C^2$$

Denoting the partial derivatives of R and Q with respect to the parameter θ as $R|_{\theta}$ and $Q|_{\theta}$ and using the above defined terms, the partial derivatives are:

$$R|_K = R/K$$

$$R|\tau = K\omega[(AD - BC) \cos \tau\omega - (AB + CD) \sin \tau\omega]/Z$$

$$R|\gamma_1 = K\omega[C \cos \tau\omega + A \sin \tau\omega]/Z$$

$$R|\gamma_2 = K\omega^2[-A \cos \tau\omega + C \sin \tau\omega]/Z$$

$$R|\gamma_3 = K\omega^3[-C \cos \tau\omega - A \sin \tau\omega]/Z$$

$$R|\alpha_1 = \omega[K(D \cos \tau\omega - B \sin \tau\omega) - 2CR]/Z$$

$$R|\alpha_2 = \omega^2[K(-B \cos \tau\omega - D \sin \tau\omega) + 2AR]/Z$$

$$R|\alpha_3 = \omega^3[K(-D \cos \tau\omega + B \sin \tau\omega) + 2CR]/Z$$

and

$$Q|_K = Q/K$$

$$Q|\tau = K\omega[-(AB + CD) \cos \tau\omega - (AD - BC) \sin \tau\omega]/Z$$

$$Q|\gamma_1 = K\omega[A \cos \tau\omega - C \sin \tau\omega]/Z$$

$$Q|\gamma_2 = K\omega^2[C \cos \tau\omega + A \sin \tau\omega]/Z$$

$$Q|\gamma_3 = K\omega^3[-A \cos \tau\omega + C \sin \tau\omega]/Z$$

$$Q|\alpha_1 = \omega[K(-B \cos \tau\omega - D \sin \tau\omega) - 2CQ]/Z$$

$$Q|\alpha_2 = \omega^2[K(-D \cos \tau\omega + B \sin \tau\omega) + 2AQ]/Z$$

$$Q|\alpha_3 = \omega^3[K(B \cos \tau\omega + D \sin \tau\omega) + 2CQ]/Z$$

APPENDIX B

LISTING OF SUBROUTINE

The following subroutine is used in conjunction with our modified version of a program for least-squares estimation of nonlinear parameters. The section for the first key puts out the labeling for the full model form and sets up the test value for the indicator of real or imaginary part. The second key section estimates the function and the residual and the third key section estimates the partial derivatives.

SUBROUTINE MODEL(KEY)

C FITTING COMPLEX VALUED TRANSFER FUNCTION: EQUAL WEIGHTS:

IMPLICIT REAL*8(A-H,O-Z)

COMMON X(300,10),Y(300),B(30),P(30),PRNT(5),HDR2(18),F,RES,NI(40),

1 I,N,K,IP,NPRNT

DIMENSION XHDR(18)

DATA XHDR/144HMODEL FOR FITTING IN THE FREQUENCY DOMAIN;S=J OMEGA

1 H(S)=K(1+G(1)S+...+G(3)S**3)EXP(-TS) / (1+A(1)

2S+...+A(3)S**3)

/

GO TO (10,20,30),KEY

10 DO 5 I=1,18

5 HDR2(I)=XHDR(I)

REAL=1.DO

RETURN

C B(1)=K

C B(2)=T

C B(3)=G(1)

C B(4)=G(2)

C B(5)=G(3)

C B(6)=A(1)

C B(7)=A(2)

C B(8)=A(3)

20 W2=X(I,1)**2

TW=B(2)*X(I,1)

A=1.DO-B(7)*W2

E=1.DO-B(4)*W2

C=X(I,1)*(B(6)-B(8)*W2)

D=X(I,1)*(B(3)-B(5)*W2)

Z=A**2+C**2

CS=DCOS(TW)

SN=DSIN(TW)

ABCD=A*E+C*D

ADBC=A*D-E*C

IF(X(I,2).GT.REAL) GO TO 25

F=B(1)*(ABCD*CS+ADBC*SN)/Z

RES=(Y(I)-F)

RETURN

25 F=B(1)*(ADBC*CS-ABCD*SN)/Z

RES=(Y(I)-F)

RETURN

30 W=X(I,1)

W3=W*W2

PK=B(1)

IF(X(I,2).GT.REAL) GO TO 35

P(1)=F/PK

P(2)=PK*W*(ADBC*CS-ABCD*SN)/Z

P(3)=PK*W*(C*CS+A*SN)/Z

P(4)=PK*W2*(C*SN-A*CS)/Z

P(5)=PK*W3*(-C*CS-A*SN)/Z

P(6)=W*(PK*(D*CS-E*SN)-2.DO*C*F)/Z

P(7)=W2*(PK*(-E*CS-D*SN)+2.DO*A*F)/Z

P(8)=W3*(PK*(-D*CS+E*SN)+2.DO*C*F)/Z

RETURN

35 P(1)=F/PK

P(2)=PK*W*(-ADBC*SN-ABCD*CS)/Z

P(3)=PK*W*(A*CS-C*SN)/Z

P(4)=PK*W2*(C*CS+A*SN)/Z

P(5)=PK*W3*(-A*CS+C*SN)/Z

P(6)=W*(PK*(-E*CS-D*SN)-2.DO*C*F)/Z

P(7)=W2*(PK*(-D*CS+E*SN)+2.DO*A*F)/Z

P(8)=W3*(PK*(E*CS D*SN)+2.DO*C*F)/Z

RETURN

END